



PRO-POLISH DENSIFIER

LIQUID HARDENER FOR CONCRETE

DESCRIPTION

PRO-POLISH DENSIFIER is a liquid concrete-floor hardener. PRO-POLISH DENSIFIER is a solution of sodium silicates designed to react with the concrete to seal the pores and chemically harden the surface.

PRIMARY APPLICATIONS

- Interior or exterior horizontal surfaces
- Offices
- Warehouse floors
- Educational or medical facilities
- Multi-residential buildings
- Food storage areas

FEATURES/BENEFITS

- Increases abrasion resistance
- Leaves no film that will wear off
- May be applied over stained/dyed concrete
- Improves chemical resistance
- Eliminates dusting
- Increases surface strength
- Resists oil and water penetration
- Treated surface is not slippery

TECHNICAL INFORMATION

Solids :	20 to 25%
pH:	12 to 13
Density:	9.8 to 10 lbs/gal (1.16 to 1.19 kg/L)
Appearance:	Clear/turbid liquid
Odor:	None
VOC:	<=5 g/L
Foot Traffic	4 to 6 hours
Can be painted	

PACKAGING

PRO-POLISH DENSIFIER is available in 5 gal (18.9 L) units and 55 gal (208.2 L) drums.

SHELF LIFE

2 Years in original, unopened containers

COVERAGE

PRO-POLISH DENSIFIER is applied at a rate of approximately 200 to 300 ft²/gal (4.9 to 7.4 m²/L)

DIRECTIONS FOR USE

PRO-POLISH DENSIFIER can be applied to any unsealed concrete surface.

Surface Preparation Newly Placed Concrete:

New concrete should be allowed to cure for a minimum of 7 days before application of densifier. Any sealers or curing compounds must be completely removed prior to use. Concrete surface must be clean and free of contamination.

Surface Preparation Existing Older Concrete:

Concrete should be free of any contaminants that would prevent penetration of the hardener. Curing compounds, sealers, paint, coatings, grease/oil, waxes and dirt must be removed. Grease and oil may be removed with GREASE-A-WAY. Concrete surface may be damp, but not puddled.

APPLICATION: PRO-POLISH DENSIFIER is ready to use from the container. Apply a single coat of PRO-POLISH DENSIFIER using a low pressure sprayer, roller, scrub pad or auto scrubber. A mechanical scrubber will increase the penetration and effectiveness of the product. Apply so that coverage results in a uniform wet surface without puddles. PRO-POLISH DENSIFIER should soak into the concrete, and any excess material should be removed with a squeegee and not allowed to dry on the surface. Dried product will need to be removed with a grinder.

PRECAUTIONS/LIMITATIONS

- Do not allow product to freeze.
- Air temperature must be above 35 °F (2 °C) and rising at the time of application.
- Do not dilute.
- Protect glass or metal from contact with PRO POLISH DENSIFIER. If accidentally over-sprayed on these surfaces, immediately wash surface with clean water.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 08.15

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.